

Transportation Signal Lenses and Accessories

General Signals' 4" LED Gate Arm Light



L-4-LED-X2Interior showing 4-LED-Board



4-LED-BOARD-SMFits any 4" gate light



L-4-LED-X2Interior showing 4-LED-Board

- LED board retrofits into any existing gate light. Standard S11 bulb base fits any gate light utilizing a standard 18 or 25 watt bulb.
- Estimated life 100,000 hours.
- Operating temp: -30° C to +45° C.
- Current draw .35 amp REF @ 10 volts vs. 1.8 or 2.5 amps for standard incandescent bulbs.
- Light output 48 (REF) lumens.
- Each side of the light board has 2 ultrabrite LEDs.
- Available as a complete gate light or as replacement boards only to retrofit existing units.
- Operating voltage 8-15V DC.

Ordering Information

4-LED-BOARD-SM	LED Board Only - will fit into any 4" gate light as a replacement for a standard 18 or 25 watt lamp	L-4-LED-X2	4" LED gate light, xenoy frame, xenoy junction box, complete with hardware
L-4-1013LED-K	LED gate light kit includes (3) 4" LED gate lights with 35' of 3-wire SJ cord	L-4-LED-PIKIT	LED gate light kit includes (3) 4" LED gate lights with pig tail connecting cords and 15' of lead wire